



ELGEF Plus Transition coupler PE/brass
d20-63mm / SDR11 / Male thread R

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit with ELGEF Plus coupler or *reducer

	d	Thread Type	Size	DN	PN	SDR	Code	Weight
	(mm)		(inch)	(mm)	(bar)			(kg)
	20	R	½	15	16	11	720 920 756	0.187
*	20	R	1	15	16	11	720 920 754	0.344
	25	R	¾	20	16	11	720 920 757	0.254
*	25	R	1	20	16	11	720 920 763	0.340
*	32	R	½	25	16	11	720 920 764	0.213
	32	R	¾	25	16	11	720 920 765	0.268
	32	R	1	25	16	11	720 920 758	0.340
	32	R	1 ¼	25	16	11	720 920 766	0.489
	32	R	1 ½	25	16	11	720 920 767	0.635
*	32	R	2	25	16	11	720 920 768	1.000
	40	R	1	32	16	11	720 920 771	0.364
	40	R	1 ¼	32	16	11	720 920 759	0.514
	40	R	1 ½	32	16	11	720 920 772	0.645
*	40	R	2	32	16	11	720 920 773	0.961
	50	R	1	40	16	11	720 920 776	0.367
	50	R	1 ¼	40	16	11	720 920 777	0.554
	50	R	1 ½	40	16	11	720 920 760	0.652
	50	R	2	40	16	11	720 920 778	0.971
	63	R	1	50	16	11	720 920 781	0.441
	63	R	1 ¼	50	16	11	720 920 782	0.600
	63	R	1 ½	50	16	11	720 920 783	0.712
	63	R	2	50	16	11	720 920 761	0.943

	d	d1	L	s	SDR pipe
	(mm)	(mm)	(mm)	(mm)	
	20	31	110	30	9-11
*	20	44	124	40	9-11
	25	36	111	35	9-11
*	25	44	124	40	9-11
*	32	44	121	30	9-11
	32	44	122	35	9-11
	32	44	117	40	9-11
	32	54	135	50	9-11
	32	60	143	60	9-11
*	32	81	157	70	9-11
	40	54	133	40	9-11
	40	54	127	50	9-11
	40	66	143	60	9-11
*	40	81	157	70	9-11
	50	66	141	40	9-11
	50	66	143	50	9-11
	50	66	135	60	9-11
	50	81	157	70	9-11
	63	81	151	40	9-11
	63	81	153	40	9-11
	63	81	153	60	9-17.6
	63	81	147	70	9-17.6

Data sheet

valid from: 6/24/21



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>